

**AMENDMENTS TO THE CLAIMS**

Please amend the claims as follows.

1. (Currently Amended) A downhole tool for collecting and retrieving junk from a well bore, the tool comprising:  
a cylindrical body attachable in a work string;  
said body having an internal throughbore, and an external sleeve located around the body defining a trap for junk.  
a multi-faceted surface comprising a plurality of projections arranged at an end of the body for contacting with and breaking up junk; and  
a plurality of inlet ports through which the broken up junk passes into ~~[[a]]~~ the trap for collection;  
wherein each projection is located between adjacent inlet ports and wherein adjacent projections define channels therebetween which are shaped to direct the junk into the respective inlet ports.
2. (Original) A downhole tool as claimed in Claim 1 wherein the projections each include a plurality of tungsten carbide coated surfaces.
3. (Currently Amended) A downhole tool as claimed in any preceding Claim wherein ~~the tool further includes a sleeve located around the body, the sleeve including~~ includes filter means for filtering debris from fluid passing there through.
4. (Currently Amended) A downhole tool as claimed in Claim 3 wherein ~~[[a]]~~ the trap is provided in an annular space between the body and the sleeve.
5. (Previously Presented) A downhole tool as claimed in any preceding Claim wherein the ports have a flow path parallel to a longitudinal axis of the tool.

6. (Previously Presented) A downhole tool as claimed in any preceding Claim wherein each inlet port includes a valve.
7. (Previously Presented) A downhole tool as claimed in any one of Claims 3 to 6 wherein the tool includes a throat, the throat being located adjacent to the projections and having a diameter narrower than a diameter of the sleeve.
8. (Currently Amended) A downhole tool as claimed in any preceding Claim wherein said throughbore in the cylindrical body includes is an axial bore to permit fluid flow through the work string.
9. (Original) A downhole tool as claimed in Claim 7 wherein the tool includes one or more milling elements located adjacent the throat and distal to the inlet ports.
10. (Currently Amended) A method of collecting and retrieving junk within a well bore, by means of circulating fluid through a workstring comprising a cylindrical body, said body having an internal throughbore, and an external sleeve located around the body defining a trap for junk, the method further comprising the steps:
  - (a) providing a multi-faceted contact surface on a work string, the surface including a plurality of projections and a plurality of inlet ports providing access to the trap, each projection being located between adjacent inlet ports;
  - (b) breaking up large pieces of junk by contact with the surface;
  - (c) directing the broken-up junk towards the inlet ports along channels defined between adjacent projections and collecting the broken-up junk through the inlet ports; and
  - (d) storing the broken-up junk in a said trap adjacent the inlet ports.
11. (Original) A method as claimed in Claim 10 wherein the method includes the steps of providing a mill ahead of the surface and jetting milled junk from the mill towards the inlet ports.

12. (Previously Presented) A method as claimed in Claim 10 or Claim 11 wherein the method includes the step of operating one or more valves at each inlet port to prevent the broken-up junk from exiting the trap.
13. (New Claim) A downhole tool for collecting and retrieving junk from a well bore, the tool comprising:
  - a cylindrical body attachable in a work string,
  - said body having an internal throughbore, and an external sleeve located around the body defining a trap for junk; and
  - a multi-faceted surface comprising a plurality of projections arranged at an end of the body for contacting with and breaking up junk; and
  - a plurality of inlet ports through which the broken up junk passes into the trap for collection wherein each projection is located between adjacent inlet ports.